



 **AUDIOLYMPIC**
ENJOY YOUR FAVORITE MUSIC



AUDIOLYMPIC  DELTA

FEATURES

Active Digital 4-way Audio System
 Active Room Compensation (A.R.C.)
 Sealed Spherical Enclosure

DIMENSIONS & WEIGHT

Height 1340 mm
 Width 400 mm
 Depth 540 mm
 Weight 80 kg

INPUTS

SPDIF (2x) 75 ohm On RCA Connector
 Optical (2x) On Toslink Connector
 AES-EBU On Balanced XLR Connector

DIGITAL MASTER/SLAVE

Maximum Input Sample Rate Up To 216 kHz
 Digital Signal Processor (2x) Powered By Analog Devices
 Dynamic Range 32 bit Floating Point (1680 dB)
 Digital Link RJ45

CONTROL

Remote Volume, Input, A.R.C., System Monitor

SPEAKER DRIVERS

Tweeter 26 mm, Beryllium, AirCirc Motor Design
 Mid 120 mm, Extremely Linear Excursion
 Woofer 180 mm, Extremely Linear Excursion
 Subwoofer 320 mm, Paper Sandwich Cone

AMPLIFIERS

Low Distortion, Wide Bandwidth, High Power Amplifier (2x2 Channels x2) THD 0.0014 % @ 2 W, Frequency Response -0.2 dB @ 20 Hz ~ 20 kHz

DIGITAL ANALOG CONVERTER

Sabre Pro ES9038pro Flagship (2x) DNR 132 dB, THD+N -122 dB

